




DEFENDER 90 · 110 · 130

FORECOURT DATA

Fuel



4-cylinder petrol engines
 V8 cylinder petrol engines
 4-cylinder diesel engines

Tank capacity
 - 90 models
 - 110 models

90 octane) 2 star ** UK rating
 minimum) unleaded or
 91 to 93 octane) leaded

Diesel fuel (DERV) (Not exceeding 1% sulphur content. See Fuel Recommendations, Section 3)

Side tank 54,58 litres (12 gallons)
 Rear tank 79,5 litres (17.5 gallons)
 Side tank (except Station wagon) 68,2 litres (15 gallons)
 Side tank (Station wagon only) 45,5 litres (10 gallons)

Engine Oil

Viscosity grade



Topping-up

15W/40 for all models. See DATA section for full details and the special oils for diesel engines.

Maintain oil level between marks on dipstick as follows:

- 4-cylinder models between 'L' and 'H' notches
- 200Tdi models between MIN and MAX notches
- V8 cylinder models between 'LOW' and 'HIGH' marks

Quantity of oil required to raise level from 'L' to 'H' or 'LOW' to 'HIGH' MIN to MAX as applicable:

- 4-cylinder models: 1,0 litre (1.75 pints)
- V8 cylinder models: 1,4 litre (2.5 pints)


Coolant



Universal anti-freeze.

See Data Section 6 for proportions of solutions.

Windscreen Washer Bottle



All Seasons Screen Washer Fluid.

Tyre Pressure

See over



WARNING: Tyre pressures must be checked with the tyres cold, as the pressure is about 0.21 bar (3 lbf/in²) 0.2 kg/cm² higher at running temperature. If the vehicle has been parked in the sun or high ambient temperatures, DO NOT reduce the tyre pressures, move the vehicle into the shade and wait for the tyres to cool before checking the pressures.

TYRE PRESSURES

Maximum tyre life and performance will only be obtained if the tyres are maintained at the correct pressures.

	Tyres - size and type		Normal	
			All load conditions	
			Front	Rear
90 M O D E L S	7.50-16 CROSS-PLY	bar	1,9	2,4
		lbf/in ²	28	35
		kgf/cm ²	2,0	2,5
	205R16 RADIAL-PLY	bar	1,9	2,4
		lbf/in ²	28	35
		kgf/cm ²	2,0	2,5
7.50R16 RADIAL-PLY	bar	1,9	2,75	
	lbf/in ²	28	40	
	kgf/cm ²	2,0	2,8	
110 M O D E L S	7.50-16 CROSS-PLY	bar	1,9	2,9
		lbf/in ²	28	42
		kgf/cm ²	2,0	3,0
	750R16 RADIAL-PLY	bar	1,9	3,3
		lbf/in ²	28	48
		kgf/cm ²	2,0	3,4